



3336 GC

Spreader Settings

16/30 Sand Carrier SGN = 78

Pounds of 3336 GC per 1000

Spreader	Speed (mph)	Swath (ft)	Cone Set	Rate Settings			
				3	6	9	12
Lesco Rotary	3	9		9	12	14	17
Cyclone	3	8		3.5	4.2	4.7	5
Scotts R-8A	3	11	4	H 1/2	J 1/2	L	M 1/2
Scotts R-8A1	3	11	4	H	J 1/2	L	M 1/2
Scotts AccuPro 2000	3	11	4	H 1/2	K	L 1/2	M 1/2
Scotts SR 2000	3	11	4	H 1/2	K	L 1/2	N
Spyker	3	8		3.5	4.2	4.7	5
PrizeLAWN CBR III & BigFOOT	3	8		F	H 1/2	J	K 1/2
PrizeLAWN CBR II	3	8		2.5	3.5	4	4.5
Earthway	3	9		16	21	26	30
Precision Broadcast	3	9		1	1 1/2	3	3 1/2
Precision Drop	3	2		0	1/2	3/4	1
Gandy Model 24	3	2		20	23	25	27
Gandy Model 36	3	3		20	23	25	27
Gandy Model 42	4.5	3 1/2		22	25	28	31
Gandy 6500 Series	4.5	4 to 8		16	23	28	32
Lely H/R (2)*	4.5	18	III-B	2.25	3	3.5	4.25
Lely W (2)*	4.5	18	III-B	2.25	3	3.5	4.25
Vicon 03 Series*	4.5	18		11	16	21	25
Vicon 03 Series*	4.5	34		16	24	30	37

* PTO @ 450 RPM

These settings are presented as a guide for use. Age, conditions of spreader and operator speed will cause variation in applied rates of material. Spreader calibration at the beginning of each application is recommended.